SIGHT

INFRA RED DOME CAMERA

DI-360DIS(FL)
DI-370DIS(FL)
DI-380DIS(FL)

B-Black

* Functionality is subject to camera model

- Elegant metal case
- 24 IR Leds
- For Day & Night Conditions
- Visible distance at dark (IR on) 15M
- 3.6mm wide-angle lens
- Indoor & Outdoor Applications

DI-360DIS(FL)
- 760H Sensor
- 650TVL
- 1/3"
- ICR

DI-370DIS(FL)
- 960H Sensor
- 700TVL
- 1/3"
- ICR

DI-380DIS(FL)
- 1.3MP Sensor
- 1/3"
- ICR

Specifications

MODEL	DI-360DIS(FL)	DI-370DIS(FL)	DI-380DIS(FL)
Image Sensor	1/3" DIS		
DSP System	Eco Sight	Pro Sight	Ultra Sight
Effective Pixels	760H (756 x 504)	960H (976 x 496)	1.3MP (1305×1049)
Scanning System	PAL/NTSC		
Horizontal Resolution	650TV Line	700TV Line	1.3 Mega pixel
Electronic Shutter	1/50 ~1/120,000 sec	1/60 ~1/120,000 sec	
Min. Illumination	0.1Lux (0 Lux IR On)		0.01Lux (0 Lux IR On)
Day & Night	Auto D&N (ICR)		
IR LED	36 LED		
Sync. System	Internal Sync.		
S/N Ratio	>50dB		>62dB
White Balance	Auto (AWB)		
Noise Reduce	2D-DNR (Auto)		
Analog Output	Composite Output 1.0Vp-pat 750 ohm		
Lens	3.6mm board lens		
Power	12V DC (±10%)		
Operation Temp	-10 ℃ to 50℃, RH 95% Max		
Dimension	(Φ)94x (H)69(mm)		
Net Weight	310G		



Round design for all directions movement